

EuroSeal

Antiquing Sealer



Description

Euroseal is a 100% Acrylic Polymer Sealer that is applied over **Europlast** finish. Euroseal can also be applied to cement stuccos, cementitious products, Brick, Block, Stone and Acrylic finishes to provide an “antique” or weathered appearance. It is highly resistant to moisture and helps to shed water in vertical wall applications while minimizing challenges associated with efflorescence. High-Gloss Euroseal is available for interior applications.

Color

Euroseal is available in clear and an unlimited selection of semi-transparent colors. This product is intended to create an old world or weathered look while adding a striking characteristic to completed walls. As such, application of Euroseal will give the wall an uneven finished color.

Container

48 pounds net weight / 5-gallon pail
9 pound / 1 gallon pail

Use

Euroseal is designed primarily to be a concrete sealer. If it is purchased tinted, Euroseal has a unique ability to transform a standard wall finish into a classic example of centuries old plaster. This semi-transparent sealer is formulated to obtain an uneven antiqued or “mottled” appearance over **Europlast** finish. Euroseal also provides a highly water-resistant surface that helps reduce dirt pick-up and control efflorescence. Euroseal may also be applied to properly cured Cement stucco, One-coat stucco, Brick, Block, Stone, even painted textured surfaces.

Surface Preparation

Substrate must be fully cured, clean, dry, and free from all loose or foreign materials prior to application.

Mixing

Using a jiffler type mixer, agitate Euroseal making sure all pigments are evenly dispersed prior to use. Do not introduce air into the product.

Clean-up

Water soluble when wet. Clean tools and equipment with water immediately after use. Dried material is very difficult to remove.

Adhesion

Excellent adhesion to properly prepared substrates.

Coverage

Approximately 800-1000 square feet per 5-gallon container, depending on substrate porosity & application method.

Drying Time

Typical dry time is 24 hours, depending on climate. Drying time can be greatly affected by low temperatures and/or high humidity. Do not allow product to freeze or allow exposure to rain while drying. Allow additional time during humid and/or cold temperatures.

Storage

Protect from freezing. Store in a cool, dry area tightly sealed. Recommended storage temperature between 40-90°F.

Shelf Life

One year, if protected from direct sunlight and freezing temperatures.

Limitations

1. Ambient and surface temperatures must be above 40°F during application and drying period.
2. Euroseal should never be used on horizontal surfaces (exceptions – ceilings, soffits, etc.).
3. Product performance is directly related to substrate integrity.
4. Euroseal is a vertical wall coating. Small areas can be sloped; those surfaces shall be minimum 4 in 12 pitch.
5. Never cover Euroseal with solvent based materials.

Application

Euroseal may be applied by brush, roller, or appropriate spray equipment. If using clear Euroseal, the most popular method is spray applying the sealer, then backrolling to ensure complete coverage. If using a tinted sealer, then smooth roller application is not recommended as the color usually darkens significantly where lap marks occur (the severity of the marks depends on the porosity of the substrate and other factors). For tinted sealer application, either a textured roller or “ragging” application methods are used; product can be sprayed on with an airless sprayer prior to those finishing techniques.

Manufacturer

Stuc-O-Flex International, Inc.
17639 NE 67th Court
Redmond, WA 98052
1-800-305-1045
1-425-885-5085
1-425-869-0107 Fax
Info@stucoflex.com (E-mail)
www.stucoflex.com (Web page)

Antiquing